


SAJ...(d 5-22)



| Seleccione Consulta | Número de rodamiento | Dimensiones (mm) | | | | | | | | | | | Clasificación de carga básica (kN) | | Peso corazón kg |
|---------------------|----------------------|------------------|-----------|----------------|-----------|----------------|----|----|--------------------|----------------|--------|------|------------------------------------|---------|-----------------|
| | | dk | segundo : | d _k | C1 máximo | d ₂ | G | h | l ₁ min | l ₂ | rs min | un° | cr | corazón | |
| SAJ5 | 5 | 8 | 11.112 | 7 | 16 | M5 | 33 | 20 | 41 | 0.3 | 7 | 2.3 | 2.5 | 0.011 | |
| SAJ6 | 6 | 9 | 12.7 | 7 | 18 | M6 | 36 | 22 | 45 | 0.3 | 11 | 3.2 | 4 | 0.015 | |
| SAJ8 | 8 | 12 | 15.875 | 9 | 22 | M8 | 42 | 25 | 53 | 0.3 | 14 | 5.3 | 7.5 | 0.03 | |
| SAJ10 | 10 | 14 | 19.05 | 11 | 26 | M10 | 48 | 29 | 61 | 0.3 | 12 | 7.3 | 10.5 | 0.048 | |
| SAJ12 | 12 | 16 | 22.225 | 12 | 30 | M12 | 54 | 33 | 69 | 0.3 | 13 | 8.5 | 13 | 0.076 | |
| SAJ14 | 14 | 19 | 25.4 | 14 | 34 | M14 | 60 | 36 | 77 | 0.3 | 14 | 12 | 17 | 0.115 | |
| SAJ16 | 16 | 21 | 28.575 | 15 | 38 | M16 | 66 | 40 | 85 | 0.3 | 15 | 16.5 | 21 | 0.159 | |
| SAJ18 | 18 | 23 | 31.75 | 17 | 42 | M18x1.5 | 72 | 44 | 93 | 0.6 | 14 | 20 | 25.5 | 0.222 | |
| SAJ20 | 20 | 25 | 34.925 | 18 | 46 | M20x1.5 | 78 | 47 | 101 | 0.6 | 14 | 23 | 30 | 0.292 | |
| SAJ22 | 22 | 28 | 38.1 | 20 | 50 | M22x1.5 | 84 | 51 | 109 | 0.6 | 15 | 27.5 | 35.5 | 0.381 | |