


# SAZP...S(d 4.83~25.4)



| Seleccione Consulta  | Número de rodamiento | Dimensiones (mm) |           |       |                       |                |        |       |                    |                |                |        |     |     | Clasificación de carga básica (kN) |  | Peso corazón kg |
|----------------------|----------------------|------------------|-----------|-------|-----------------------|----------------|--------|-------|--------------------|----------------|----------------|--------|-----|-----|------------------------------------|--|-----------------|
|                      |                      | dk               | segundo : | dk    | C <sub>1</sub> máximo | d <sub>2</sub> | G      | h     | l <sub>1</sub> min | l <sub>2</sub> | l <sub>7</sub> | rs min | un° | cr  | corazón                            |  |                 |
| SAZP4S <sup>1)</sup> | 4.83                 | 7.92             | n.i       | 6.35  | 15.88                 | 10-32          | 31.75  | 19.05 | 39.7               | —              | 3              | 10     | 3.4 | 3.8 | 0.013                              |  |                 |
| SAZP4S <sup>1)</sup> | 0.19                 | 0.312            | 0.437     | 0.25  | 0.625                 | 10-32          | 1.25   | 0.75  | 1.563              | —              | 0.012          | 10     | 3.4 | 3.8 | 0.013                              |  |                 |
| SAZP6S <sup>1)</sup> | 6.35                 | 9.53             | 12.7      | 7.14  | 19.05                 | 1/4-28         | 39.67  | 25.4  | 49.2               | —              | 0.3            | 13     | 4.5 | 6.6 | 0.022                              |  |                 |
| SAZP6S <sup>1)</sup> | 0.25                 | 0.375            | 0.5       | 0.281 | 0.75                  | 1/4-28         | 1.562  | 1     | 1.937              | —              | 0.012          | 13     | 4.5 | 6.6 | 0.022                              |  |                 |
| SAZP7S               | 7.94                 | 11.1             | 15.88     | 8.74  | 22.23                 | 5/16-24        | 47.63  | 31.75 | 58.72              | —              | 0.3            | 10     | 6.9 | 8.4 | 0.037                              |  |                 |
| SAZP7S               | 0.3125               | 0.437            | 0.625     | 0.344 | 0.875                 | 5/16-24        | 1.875  | 1.25  | 2.312              | —              | 0.012          | 10     | 6.9 | 8.4 | 0.037                              |  |                 |
| SAZP9S               | 9.53                 | 12.7             | 18.26     | 10.31 | 25.4                  | 3/8-24         | 49.23  | 31.75 | 61.93              | —              | 0.6            | 9      | 9.4 | 10  | 0.055                              |  |                 |
| SAZP9S               | 0.375                | 0.5              | 0.719     | 0.406 | 1                     | 3/8-24         | 1.938  | 1.25  | 2.438              | —              | 0.024          | 9      | 9.4 | 10  | 0.055                              |  |                 |
| SAZP11S              | 11.11                | 14.27            | 20.62     | 11.1  | 28.58                 | 7/16-20        | 53.98  | 34.93 | 68.28              | —              | 0.6            | 11     | 11  | 13  | 0.078                              |  |                 |
| SAZP11S              | 0.4375               | 0.562            | 0.812     | 0.437 | 1.125                 | 7/16-20        | 2.125  | 1.375 | 2.688              | —              | 0.024          | 11     | 11  | 13  | 0.078                              |  |                 |
| SAZP12S              | 12.7                 | 15.88            | 23.81     | 12.7  | 33.32                 | 1/2-20         | 61.93  | 38.1  | 78.59              | —              | 0.6            | 9      | 15  | 19  | 0.12                               |  |                 |
| SAZP12S              | 0.5                  | 0.625            | 0.937     | 0.5   | 1.312                 | 1/2-20         | 2.438  | 1.5   | 3.094              | —              | 0.024          | 9      | 15  | 19  | 0.12                               |  |                 |
| SAZP15S              | 15.88                | 19.05            | 28.58     | 14.27 | 38.1                  | 5/8-18         | 66.68  | 41.28 | 85.73              | 18.2           | 0.6            | 11     | 20  | 21  | 0.18                               |  |                 |
| SAZP15S              | 0.625                | 0.75             | 1.125     | 0.562 | 1.5                   | 5/8-18         | 2.625  | 1.625 | 3.375              | 0.717          | 0.024          | 11     | 20  | 21  | 0.18                               |  |                 |
| SAZP19S              | 19.05                | 22.23            | 33.32     | 17.45 | 44.45                 | 3/4-16         | 73.03  | 44.45 | 95.25              | 20.9           | 0.6            | 10     | 29  | 29  | 0.29                               |  |                 |
| SAZP19S              | 0.75                 | 0.875            | 1.312     | 0.687 | 1.75                  | 3/4-16         | 2.875  | 1.75  | 3.75               | 0.823          | 0.024          | 10     | 29  | 29  | 0.29                               |  |                 |
| SAZP25S              | 25.4                 | 34.93            | 47.63     | 25.4  | 69.85                 | 5/4-12         | 104.78 | 53.98 | 139.7              | 33.9           | 0.6            | 14     | 60  | 101 | 1.1                                |  |                 |
| SAZP25S              | 1                    | 1.375            | 1.875     | 1     | 2.75                  | 5/4-12         | 4.125  | 2.125 | 5.5                | 1.335          | 0.024          | 14     | 60  | 101 | 1.1                                |  |                 |