

SAZP...S(d 4.83~25.4)

| Seleccione Consulta | Número de rodamiento | Dimensiones (mm) | | | | | | | | | | | | | Clasificación de carga básica (kN) | | Peso corazón kg |
|----------------------|----------------------|------------------|-----------|----------------|-----------------------|----------------|--------|-------|--------------------|----------------|----------------|--------------------|-----|-----|------------------------------------|--|-----------------|
| | | dk | segundo : | d _k | C ₁ máximo | d ₂ | G | h | l ₁ min | l ₂ | l ₇ | r _s min | un° | cr | corazón | | |
| SAZP4S ¹⁾ | 4.83 | 7.92 | n.i | 6.35 | 15.88 | 10-32 | 31.75 | 19.05 | 39.7 | — | 3 | 10 | 3.4 | 3.8 | 0.013 | | |
| SAZP4S ¹⁾ | 0.19 | 0.312 | 0.437 | 0.25 | 0.625 | 10-32 | 1.25 | 0.75 | 1.563 | — | 0.012 | 10 | 3.4 | 3.8 | 0.013 | | |
| SAZP6S ¹⁾ | 6.35 | 9.53 | 12.7 | 7.14 | 19.05 | 1/4-28 | 39.67 | 25.4 | 49.2 | — | 0.3 | 13 | 4.5 | 6.6 | 0.022 | | |
| SAZP6S ¹⁾ | 0.25 | 0.375 | 0.5 | 0.281 | 0.75 | 1/4-28 | 1.562 | 1 | 1.937 | — | 0.012 | 13 | 4.5 | 6.6 | 0.022 | | |
| SAZP7S | 7.94 | 11.1 | 15.88 | 8.74 | 22.23 | 5/16-24 | 47.63 | 31.75 | 58.72 | — | 0.3 | 10 | 6.9 | 8.4 | 0.037 | | |
| SAZP7S | 0.3125 | 0.437 | 0.625 | 0.344 | 0.875 | 5/16-24 | 1.875 | 1.25 | 2.312 | — | 0.012 | 10 | 6.9 | 8.4 | 0.037 | | |
| SAZP9S | 9.53 | 12.7 | 18.26 | 10.31 | 25.4 | 3/8-24 | 49.23 | 31.75 | 61.93 | — | 0.6 | 9 | 9.4 | 10 | 0.055 | | |
| SAZP9S | 0.375 | 0.5 | 0.719 | 0.406 | 1 | 3/8-24 | 1.938 | 1.25 | 2.438 | — | 0.024 | 9 | 9.4 | 10 | 0.055 | | |
| SAZP11S | 11.11 | 14.27 | 20.62 | 11.1 | 28.58 | 7/16-20 | 53.98 | 34.93 | 68.28 | — | 0.6 | 11 | 11 | 13 | 0.078 | | |
| SAZP11S | 0.4375 | 0.562 | 0.812 | 0.437 | 1.125 | 7/16-20 | 2.125 | 1.375 | 2.688 | — | 0.024 | 11 | 11 | 13 | 0.078 | | |
| SAZP12S | 12.7 | 15.88 | 23.81 | 12.7 | 33.32 | 1/2-20 | 61.93 | 38.1 | 78.59 | — | 0.6 | 9 | 15 | 19 | 0.12 | | |
| SAZP12S | 0.5 | 0.625 | 0.937 | 0.5 | 1.312 | 1/2-20 | 2.438 | 1.5 | 3.094 | — | 0.024 | 9 | 15 | 19 | 0.12 | | |
| SAZP15S | 15.88 | 19.05 | 28.58 | 14.27 | 38.1 | 5/8-18 | 66.68 | 41.28 | 85.73 | 18.2 | 0.6 | 11 | 20 | 21 | 0.18 | | |
| SAZP15S | 0.625 | 0.75 | 1.125 | 0.562 | 1.5 | 5/8-18 | 2.625 | 1.625 | 3.375 | 0.717 | 0.024 | 11 | 20 | 21 | 0.18 | | |
| SAZP19S | 19.05 | 22.23 | 33.32 | 17.45 | 44.45 | 3/4-16 | 73.03 | 44.45 | 95.25 | 20.9 | 0.6 | 10 | 29 | 29 | 0.29 | | |
| SAZP19S | 0.75 | 0.875 | 1.312 | 0.687 | 1.75 | 3/4-16 | 2.875 | 1.75 | 3.75 | 0.823 | 0.024 | 10 | 29 | 29 | 0.29 | | |
| SAZP25S | 25.4 | 34.93 | 47.63 | 25.4 | 69.85 | 5/4-12 | 104.78 | 53.98 | 139.7 | 33.9 | 0.6 | 14 | 60 | 101 | 1.1 | | |
| SAZP25S | 1 | 1.375 | 1.875 | 1 | 2.75 | 5/4-12 | 4.125 | 2.125 | 5.5 | 1.335 | 0.024 | 14 | 60 | 101 | 1.1 | | |