


SAZP...N(d 4.83□19.05)



| Seleccione Consulta | Número de rodamiento |       | Dimensiones (mm) |                |                   |                |       |       |                   |                |                |                    |      |      | Clasificación de carga básica (kN) |  | Peso corazón kg |
|---------------------|----------------------|-------|------------------|----------------|-------------------|----------------|-------|-------|-------------------|----------------|----------------|--------------------|------|------|------------------------------------|--|-----------------|
|                     | Bearing number       | dk    | segundo :        | d <sub>k</sub> | C <sub>1max</sub> | d <sub>2</sub> | G     | h     | l <sub>1min</sub> | l <sub>2</sub> | l <sub>7</sub> | r <sub>s min</sub> | α° ≈ | cr   |                                    |  |                 |
| SAZP4N              | 4.83                 | 7.92  | 11.1             | 6.35           | 15.88             | 10-32          | 31.75 | 19.05 | 39.7              | —              | 0.3            | 10                 | 3.3  | 5.38 | 0.013                              |  |                 |
| SAZP4N              | 0.19                 | 0.312 | 0.437            | 0.25           | 0.625             | 10-32          | 1.25  | 0.75  | 1.563             | —              | 0.012          | 10                 | 3.3  | 5.38 | 0.013                              |  |                 |
| SAZP6N              | 6.35                 | 9.53  | 12.7             | 7.14           | 19.05             | 1/4-28         | 39.67 | 25.4  | 49.2              | —              | 0.3            | 13                 | 6.8  | 10.9 | 0.022                              |  |                 |
| SAZP6N              | 0.25                 | 0.375 | 0.5              | 0.281          | 0.75              | 1/4-28         | 1.562 | 1     | 1.937             | —              | 0.012          | 13                 | 6.8  | 10.9 | 0.022                              |  |                 |
| SAZP7N              | 7.94                 | 11.1  | 15.88            | 8.74           | 22.23             | 5/16-24        | 47.63 | 31.75 | 58.72             | —              | 0.3            | 10                 | 7.6  | 12.2 | 0.037                              |  |                 |
| SAZP7N              | 0.3125               | 0.437 | 0.625            | 0.344          | 0.875             | 5/16-24        | 1.875 | 1.25  | 2.312             | —              | 0.012          | 10                 | 7.6  | 12.2 | 0.037                              |  |                 |
| SAZP9N              | 9.53                 | 12.7  | 18.26            | 10.31          | 25.4              | 3/8-24         | 49.23 | 31.75 | 61.93             | —              | 0.6            | 9                  | 11.9 | 18.7 | 0.055                              |  |                 |
| SAZP9N              | 0.375                | 0.5   | 0.719            | 0.406          | 1                 | 3/8-24         | 1.938 | 1.25  | 2.438             | —              | 0.024          | 9                  | 11.9 | 18.7 | 0.055                              |  |                 |
| SAZP11N             | 11.11                | 14.27 | 20.62            | 11.1           | 28.58             | 7/16-20        | 53.98 | 34.93 | 68.28             | —              | 0.6            | 11                 | 17.4 | 23.8 | 0.078                              |  |                 |
| SAZP11N             | 0.4375               | 0.562 | 0.812            | 0.437          | 1.125             | 7/16-20        | 2.125 | 1.375 | 2.688             | —              | 0.024          | 11                 | 17.4 | 23.8 | 0.078                              |  |                 |
| SAZP12N             | 12.7                 | 15.88 | 23.81            | 12.7           | 33.32             | 1/2-20         | 61.93 | 38.1  | 78.59             | —              | 0.6            | 9                  | 19.9 | 28.6 | 0.12                               |  |                 |
| SAZP12N             | 0.5                  | 0.625 | 0.937            | 0.5            | 1.312             | 1/2-20         | 2.438 | 1.5   | 3.094             | —              | 0.024          | 9                  | 19.9 | 28.6 | 0.12                               |  |                 |
| SAZP15N             | 15.88                | 19.05 | 28.58            | 14.27          | 38.1              | 5/8-18         | 66.68 | 41.28 | 85.73             | 18.2           | 0.6            | 11                 | 22.9 | 36.9 | 0.18                               |  |                 |
| SAZP15N             | 0.625                | 0.75  | 1.125            | 0.562          | 1.5               | 5/8-18         | 2.625 | 1.625 | 3.375             | 0.717          | 0.024          | 11                 | 22.9 | 36.9 | 0.18                               |  |                 |
| SAZP19N             | 19.05                | 22.23 | 33.32            | 17.45          | 44.45             | 3/4-16         | 73.03 | 44.45 | 95.25             | 20.9           | 0.6            | 10                 | 30.2 | 48.5 | 0.29                               |  |                 |
| SAZP19N             | 0.75                 | 0.875 | 1.312            | 0.687          | 1.75              | 3/4-16         | 2.875 | 1.75  | 3.75              | 0.823          | 0.024          | 10                 | 30.2 | 48.5 | 0.29                               |  |                 |