

SIK...C(d 5□20)



Seleccione Consulta	Número de rodamiento Bearing number	Dimensiones (mm)															Clasificación de carga básica (kN)		Peso corazón kg	
		dk	segundo :	d _k	C _{1 max}	d ₂	G 6H	h ₁	l _{3 min}	l ₄	l ₅	l ₇	W	d ₃	d ₄	r _{s min}	α°≈	cr		corazón
SIK5C	5	8	11.112	6	19.5	M5	30	12	39.8	5	9.5	10	10	13	0.3	4	3.6	4.6	0.024	
SIK6C	6	9	12.7	7.5	21.2	M6	30	9	40.7	5	11	10	10	13	0.3	9	4.7	5.2	0.028	
SIK8C	8	12	15.88	9.5	25.5	M8	36	12	48.8	5	13	13	12.5	16	0.3	12	7.6	8.2	0.053	
SIK10C	10	14	19.05	11.5	31	M10	43	19	58.6	6.5	16	16	15	19	0.3	10	12	15	0.11	
SIK12C	12	16	22.23	12.5	34	M12	50	23	67	6.5	18	18	17.5	22	0.3	12	14	19	0.14	
SIK14C	14	19	25.4	14.5	38	M14	57	23	76	8	20	21	20	25	0.3	14	19	24	0.2	
SIK16C	16	21	28.58	15.5	42	M16	64	24	85	8	21	24	22	27	0.3	14	23	29	0.25	
SIK18C	18	23	31.75	17.5	46	M18×1.5	71	27	94	10	22.5	27	25	31	0.6	13	29	34	0.35	
SIK20C	20	25	34.93	18.5	50	M20×1.5	77	30	102	10	25	30	27.5	34	0.6	14	34	40	0.43	